



PA *Presse Plieuse
hydraulique
synchronisée*





PA 13530

Modèle		PA 6020	PA 9025	PA 13530	PA 16030	PA 16040	PA 22030	PA 22040
Capacité	kN	600	900	1350	1600	1600	2200	2200
Longueur utile	mm	2000	2500	3000	3000	4000	3000	4000
Distance entre montant	mm	1550	2050	2550	2550	3150	2550	3150
Course maxi	mm	250	250	250	250	250	250	250
Ouverture maxi sans outils	mm	500	500	500	500	500	500	500
Col de cygne	mm	400	400	400	400	400	400	400
Puissance moteur	kW	5,5	7,5	15	15	15	15	15
Vitesse d'approche	mm/s	150	150	150	150	150	130	130
Vitesse de travail	mm/s	9	9	10	10	10	8	8
Vitesse de retour	mm/s	120	120	105	105	105	85	85
Course X	mm	625	625	625	625	625	625	625
Vitesse X *	mm/s	350	-	-	-	-	-	-
Vitesse X **	mm/s	800	800	800	800	800	800	800
Course R	mm	200	200	200	200	200	200	200
Vitesse R	mm/s	200	200	200	200	200	200	200
Course Z - Z1 / Z2	mm	90 a 1150	90 a 1650	90 a 2150	90 a 2150	90 a 2750	90 a 2150	90 a 2750
Vitesse Z - Z1 / Z2	mm/s	1200	1200	1200	1200	1200	1200	1200
Course X1	mm	± 100	± 100	± 100	± 100	± 100	± 100	± 100
SVitesse X1	mm/s	100	100	100	100	100	100	100

(*) Machines avec seulement X (**) Machines avec X et R



SOCFLAFORM Distributeur ADIRA

ZA le terminal

3 rue gracchus Babeuf, 93135

Noisy le Sec Cedex

Tel : 01.48.43.50.50

Fax : 01.48.43.95.99

