



GH *Cisaille
hydraulique à
coupe oscillante*





GH CENTRE DE CISAILLAGE AUTOMATIQUE

Modèle		00420	00630	00640	00660	01030	01040	01330	01340	01360
Capacité de coupe										
Acier doux (45daN/mm)	mm	4	6,5	6,5	6,5	10	10	13	13	13
Acier inoxydable (70daN/mm ²)	mm	2,5	4	4	4	6,5	6,5	8	8	8
Longueur utile	mm	2050	3080	4080	6100	3080	4080	3080	4080	6120
Col de cygne	mm	260	260	260	260	260	260	260	260	260
Angle de coupe	°	11/6	11/3	11/3	11/16	13/4	13/4	13/4	13/4	11/2
Réglage du jeu entre lames.	mm	0.05-0.6	0.05-1.1	0.05-1.1	0.05-1.2	0.05-1.6	0.05-1.6	0.05-2	0.05-2	0.05-2
Puissance moteur	kW	11	15	15	15	15	15	18	18	18
Nombre de presse tôle	-	9	13	19	25	13	19	13	19	25
Longueur de la butée	mm	1000	1000	1000	1000	1000	1000	1000	1000	1000
Coups/Minute	cps/min	38	24	21	19	12	10	10	8	6
Dimensions (CE - configuration)										
Longueur	mm	2750	3750	4790	6840	3780	4800	3780	4800	6850
Profondeur	mm	2470	2480	2480	2580	2500	2600	2650	2700	2750
Profondeur pour transport	mm	2170	2180	2180	2280	2200	2300	2350	2400	2450
Hauteur	mm	1700	1730	1825	2070	1880	2000	2000	2100	2345
Poids	kg	3900	5800	8900	17000	8900	12500	11000	15000	31000



SOCCLAFORM Distributeur ADIRA
 ZA le terminal
 3 rue gracchus Babeuf, 93135
 Noisy le Sec Cedex
 Tel : 01.48.43.50.50
 Fax : 01.48.43.95.99

